

AMENDMENTS TO THE CLAIMS

1. (Canceled).

2. (Currently Amended) The composition assist frame selecting method for the digital camera as defined in ~~claim 1~~claim 18, wherein the plurality of shooting modes include at least two of an automatic shooting mode, a day scenic shooting mode, a person shooting mode and a night scenic shooting mode.

3.-4. (Canceled).

5. (Currently Amended) The composition assist frame selecting method for the digital camera as defined in ~~claim 4~~claim 20, wherein the plurality of shooting modes include at least two of an automatic shooting mode, a day scenic shooting mode, a person shooting mode and a night scenic shooting mode.

6. (Currently Amended) A digital camera comprising:

a shooting mode selecting device that ~~selects~~enables
selection of a shooting mode from a plurality of shooting modes;

an imaging device that images a subject in the shooting mode selected by the shooting mode selecting device and outputs image signals;

an image displaying device that displays the image according to the image signals outputted from the imaging device;

a storing device that stores data of a plurality of composition assist frames;

an extracting device that extracts one or more composition assist frames that can be selected from the plurality of composition assist frames according to the shooting mode selected by the shooting mode selecting device;

a composition assist frame selecting device that ~~selects~~ enables selection of a composition assist frame from the composition assist frames extracted by the extracting device; and

a composition assist frame displaying device that displays the composition assist frame selected by the composition assist frame selecting device on the image displaying device displaying the image.

7. (Original) The digital camera as defined in claim 6, wherein the plurality of shooting modes include at least two of an automatic shooting mode, a day scenic shooting mode, a person shooting mode and a night scenic shooting mode.

8. (Original) The digital camera as defined in claim 6, further comprising a luminance determining device that determines subject luminance by weighting areas of the image according to the shooting mode selected by the shooting mode selecting device, the imaging device controlling exposure according to the subject luminance determined by the luminance determining device.

9. (Original) The digital camera as defined in claim 8, wherein the luminance determining device corrects the subject luminance according to the shooting mode selected by the shooting mode selecting device.

10. (Original) The digital camera as defined in claim 6, further comprising a storage device that stores the image signals outputted from the imaging device in a storage medium.

11. (Currently Amended) A digital camera comprising:

an imaging device that images a subject and outputs image signals;

an image displaying device that displays the image according to the image signals outputted from the imaging device;

a storing device that stores data of a plurality of composition assist frames;

a direction determining device that determines whether the digital camera is held widthwise or lengthwise;

an extracting device that extracts one or more composition assist frames that can be selected from the plurality of composition assist frames according to the direction of the camera determined by the direction determining device;

a composition assist frame selecting device that ~~selects~~ enables selection of a composition assist frame from the composition assist frames extracted by the extracting device; and

a composition assist frame displaying device that displays the composition assist frame selected by the composition assist frame selecting device on the image displaying device displaying the image.

12. (Original) The digital camera as defined in claim 11, further comprising a storage device that stores the image signals outputted from the imaging device in a storage medium.

13. (Currently Amended) A digital camera comprising:

a shooting mode selecting device that ~~selects~~ enables selection of a shooting mode from a plurality of shooting modes;

an imaging device that images a subject in the shooting mode selected by the shooting mode selecting device and outputs image signals;

an image displaying device that displays the image according to the image signals outputted from the imaging device;

a storing device that stores data of a plurality of composition assist frames;

a direction determining device that determines whether the digital camera is held widthwise or lengthwise;

an extracting device that extracts one or more composition assist frames that can be selected from the plurality of composition assist frames according to the shooting mode selected by the shooting mode selecting device and the direction of the camera determined by the direction determining device;

a composition assist frame selecting device that ~~selects~~ enables selection of a composition assist frame from the composition assist frames extracted by the extracting device; and

a composition assist frame displaying device that displays the composition assist frame selected by the composition assist frame selecting device on the image displaying device displaying the image.

14. (Original) The digital camera as defined in claim 13, wherein the plurality of shooting modes include at least two of an automatic shooting mode, a day scenic shooting mode, a person shooting mode and a night scenic shooting mode.

15. (Original) The digital camera as defined in claim 13, further comprising a luminance determining device that determines subject luminance by weighting areas of the image according to the shooting mode selected by the shooting mode selecting device, the imaging device controlling exposure according to the subject luminance determined by the luminance determining device.

16. (Original) The digital camera as defined in claim 15, wherein the luminance determining device corrects the subject luminance according to the shooting mode selected by the shooting mode selecting device.

17. (Original) The digital camera as defined in claim 13, further comprising a storage device that stores the image signals outputted from the imaging device in a storage medium.

18. (New) A composition assist frame selecting method for a digital camera, the method comprising:

determining a shooting mode from a plurality of shooting modes;

extracting at least one composition assist frame associated with the selected shooting mode from a plurality of composition assist frames;

enabling selection of a composition assist frame from the at least one extracted composition assist frame associated with the selected shooting mode; and

displaying the selected composition assist frame to assist composition.

19. (New) A composition assist frame selecting method for a digital camera, the method comprising:

determining whether the digital camera is held widthwise or lengthwise;

extracting at least one composition assist frame associated with the determined direction of the digital camera from a plurality of composition assist frames;

enabling selection of a composition assist frame from the at least one extracted composition assist frame associated with the determined direction of the digital camera; and

displaying the selected composition assist frame to assist composition.

20. (New) A composition assist frame selecting method for a digital camera, the method comprising:

determining device that determines whether the digital camera is held widthwise or lengthwise;

determining a shooting mode from a plurality of shooting modes;

extracting at least one composition assist frame that can be selected from the plurality of composition assist frames associated with the determined shooting mode and the determined direction of the digital camera;

enabling selection of a composition assist frame from the at least one extracted composition assist frame associated with the determined shooting mode and the determined direction of the digital camera; and

displaying the selected composition assist frame to assist composition.

21. (New) The method of claim 18, wherein each of the plurality of composition assist frames circumscribes an area within the display.

22. (New) The method of claim 18, wherein a plurality of composition frames associated with the shooting mode are extracted.